



## HMRZ.EX26586 Gate Valves

[Page Bottom](#)

### Gate Valves

[See General Information for Gate Valves](#)

#### FULLBLAZE LIMITED

EX26586

Oxford business Park North  
7200 The Quorum  
Garsington Road  
Oxford, OX4 2JZ UNITED KINGDOM

Pattern	Model	Size, in.	End Configuration	Rated Pressure, psig
OS&Y	FB1000-300	2, 2.5, 3, 4, 5, 6, 8, 10, 12	F by F (ANSI Flange)	300
OS&Y	FB1000-250	2, 2.5, 3, 4, 5, 6, 8, 10, 12	F by F (ANSI Flange)	250
OS&Y	FB1000-200	2, 2.5, 3, 4, 5, 6, 8, 10, 12	F by F (ANSI Flange)	200
OS&Y	FB1000-PN16	2, 2.5, 3, 4, 5, 6, 8	F by F (BS Flange)	300
OS&Y	FB1000-PN16-250	10, 12	F by F (BS Flange)	250
OS&Y	FB1000-PN16-200	2, 2.5, 3, 4, 5, 6, 8, 10, 12	F by F (BS Flange)	200
NRS	FB2000-300	2.5, 3, 4, 5, 6, 8, 10, 12	F by F (ANSI Flange)	300
NRS	FB2000-250	2.5, 3, 4, 5, 6, 8, 10, 12	F by F (ANSI Flange)	250
NRS	FB2000-200	2.5, 3, 4, 5, 6, 8, 10, 12	F by F (ANSI Flange)	200
NRS	FB2000-PN16	2.5, 3, 4, 5, 6, 8	F by F (BS Flange)	300
NRS	FB2000-PN16-250	10, 12	F by F (BS Flange)	250
NRS	FB2000-PN16-200	2.5, 3, 4, 5, 6, 8, 10, 12	F by F (BS Flange)	200
OS&Y	FB1100-300	2, 2.5, 3, 4, 5, 6, 8, 10, 12	G by G	300
OS&Y	FB1100-250	2, 2.5, 3, 4, 5, 6, 8, 10, 12	G by G	250
OS&Y	FB1100-200	2, 2.5, 3, 4, 5, 6, 8, 10, 12	G by G	200
OS&Y	FB1100-PN16	2, 2.5, 3, 4, 5, 6, 8	G by G	300
OS&Y	FB1100-PN16-250	10, 12	G by G	250
OS&Y	FB1100-PN16-200	2, 2.5, 3, 4, 5, 6, 8, 10, 12	G by G	200
NRS	FB2100-300	2.5, 3, 4, 5, 6, 8, 10, 12	G by G	300
NRS	FB2100-250	2.5, 3, 4, 5, 6, 8, 10, 12	G by G	250
NRS	FB2100-200	2.5, 3, 4, 5, 6, 8, 10, 12	G by G	200
NRS	FB2100-PN16	2.5, 3, 4, 5, 6, 8	G by G	300
NRS	FB2100-PN16-250	10, 12	G by G	250
NRS	FB2100-PN16-200	2.5, 3, 4, 5, 6, 8, 10, 12	G by G	200
OS&Y	FB1200-300	2, 2.5, 3, 4, 5, 6, 8, 10, 12	F by G (ANSI Flange)	300
OS&Y	FB1200-250	2, 2.5, 3, 4, 5, 6, 8, 10, 12	F by G (ANSI Flange)	250

OS&Y	FB1200-200	2, 2.5, 3, 4, 5, 6, 8, 10, 12	F by G (ANSI Flange)	200
OS&Y	FB1200-PN16	2, 2.5, 3, 4, 5, 6, 8	F by G (BS Flange)	300
OS&Y	FB1200-PN16-250	10, 12	F by G (BS Flange)	250
OS&Y	FB1200-PN16-200	2, 2.5, 3, 4, 5, 6, 8, 10, 12	F by G (BS Flange)	200
NRS	FB2200-300	2.5, 3, 4, 5, 6, 8, 10, 12	F by G (ANSI Flange)	300
NRS	FB2200-250	2.5, 3, 4, 5, 6, 8, 10, 12	F by G (ANSI Flange)	250
NRS	FB2200-200	2.5, 3, 4, 5, 6, 8, 10, 12	F by G (ANSI Flange)	200
NRS	FB2200-PN16	2.5, 3, 4, 5, 6, 8	F by G (BS Flange)	300
NRS	FB2200-PN16-250	10, 12	F by G (BS Flange)	250
NRS	FB2200-PN16-200	2.5, 3, 4, 5, 6, 8, 10, 12	F by G (BS Flange)	200

Last Updated on 2014-09-03

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2015 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2015 UL LLC".