



GFGV.EX26590 Foam Liquid Concentrates

[Page Bottom](#)

Foam Liquid Concentrates

[See General Information for Foam Liquid Concentrates](#)

FULLBLAZE LIMITED

EX26590

Oxford business Park North
7200 The Quorum
Garsington Road
Oxford, OX4 2JZ UNITED KINGDOM

FULLBLAZE 3% AFFF, nominal 3 percent Aqueous Film Forming Foam, +35 F minimum storage and use temperature. Hydrocarbon fuels only.

FULLBLAZE 6% AFFF, nominal 6 percent Aqueous Film Forming Foam, +35 F minimum storage and use temperature. Hydrocarbon fuels only.

FULLBLAZE m 1% AFFF, nominal 1 percent Aqueous Film Forming Foam, +35 F min storage and use temperature. Hydrocarbon fuels only.

FULLBLAZE 3% Fluoroprotein, nominal 3 percent, +35 F minimum storage and use temperature. Hydrocarbon fuels only.

FULLBLAZE 6% Fluoroprotein, nominal 6 percent, +35 F minimum storage and use temperature. Hydrocarbon fuels only.

FULLBLAZE 3% FFFP, nominal 3 percent Film Forming Fluoroprotein Foam, +20 F min storage and use temperature. Hydrocarbon fuels only.

FULLBLAZE 6% FFFP, nominal 6 percent Film Forming Fluoroprotein Foam, +20 F min storage and use temperature. Hydrocarbon fuels only.

FULLBLAZE 3 x 6 AR-AFFF, nominal 3 or 6 percent Alcohol Resistant Aqueous Film Forming Foam, +35 F min storage and use temperature. Hydrocarbon fuels at 3 percent. Polar solvent fuels at 6 percent.

FULLBLAZE ECOPLUS AR/AFFF 3x3, nominal 3 percent Alcohol Resistant Aqueous Film Forming Foam, +35 F min storage and use temperature. Hydrocarbon fuels at 3 percent. Polar solvent fuels at 3 percent.

Foam concentrates for use with the following equipment.

FULLBLAZE 3% AFFF, 3 PERCENT

PROPORTIONERS - PORTABLE IN-LINE INDUCTORS

Angus Fire (UK), Model UNI225, 2-1/2 in. size, set at 3, inlet pressure of 149 psi with 30m (98 ft) of 2-1/2 in. hose between inductor and Angus Fire (UK), Model F225U nozzle

NOZZLES

Description	Size In.	Inlet Pressure psi
Angus Fire (UK), Model F225U	2-1/2	85

PROPORTIONERS - FIXED IN-LINE INDUCTORS

Description	Size In.	Orifice Diam In.	Inlet Pressure psi	Back Pressure psi
Angus, Model IND-40	1-1/2	0.13 (3.4 mm)	123	43

FIXED FOAM DISCHARGE OUTLETS

Description	Size In.	Inlet Pressure psi
Angus, Model TPS-50MKV	0.59 (15mm)	43

FOAM WATER SPRINKLERS

Fuel	Style	Min Application Rate GPM/Sq Ft	Min Inlet Pressure psi
Tyco Fire, Model B1			

Hydrocarbons	Pendant	0.16	30
--------------	---------	------	----

FOAM MONITORS

Monitor Model	Nozzle Model	Type	Monitor Inlet Pressure, psi
Newage Fire Fighting Co Ltd			
AFM-1000-750-500GPM	AFM-1000-750-500GPM at 500	Self- Inducting	100
AFM-1000-750-500GPM	AFM-1000-750-500GPM at 750	Self- Inducting	100
AFM-1000-750-500GPM	AFM-1000-750-500GPM at 1000	Self- Inducting	100
AFM-1000-750-500GPM	AFN-1000-750-500GPM at 500	With JRCP Model JRCP-1000-750-500GPM	100
AFM-1000-750-500GPM	AFN-1000-750-500GPM at 750	With JRCP Model JRCP-1000-750-500GPM	100
AFM-1000-750-500GPM	AFN-1000-750-500GPM at 1000	With JRCP Model JRCP-1000-750-500GPM	100
AFM-2000-1500-1000GPM	AFN-2000-1500-1000GPM at 1000	Self- Inducting	100
AFM-2000-1500-1000GPM	AFN-2000-1500-1000GPM at 1500	Self- Inducting	100
AFM-2000-1500-1000GPM	AFN-2000-1500-1000GPM at 2000	Self- Inducting	100
AFM-2000-1500-1000GPM	AFN-2000-1500-1000GPM at 1000	With JRCP Model JRCP-2000-1500-1000GPM	100
AFM-2000-1500-1000GPM	AFN-2000-1500-1000GPM at 1500	With JRCP Model JRCP-2000-1500-1000GPM	100
AFM-2000-1500-1000GPM	AFN-2000-1500-1000GPM at 2000	With JRCP Model JRCP-2000-1500-1000GPM	100
AFM-4000-3000-2000 GPM	AFN-4000-3000-2000 GPM at 2000	(With JRCP Model JRCP-2000-1500 GPM)	100
AFM-4000-3000-2000 GPM	AFN-4000-3000-2000 GPM at 3000	(With JRCP Model JRCP-2000-1500 GPM)	100
AFM-4000-3000-2000 GPM	AFN-4000-3000-2000 GPM at 4000	(With JRCP Model JRCP-2000-1500 PM)	100
AFM-GT-750 GPM	AFN-750 GPM	Self-Inducting	100
AFM-MI-750-GPM	AFN-750 GPM	Self-Inducting	100
AFM-GT-750-500 GPM	AFN-750-500 GPM at 750	Self-Inducting	100
AFM-GT-750-500 GPM	AFN-750-500 GPM at 500	Self-Inducting	100
AFM-GT-1000 GPM	AFN-1000 GPM	Self-Inducting	100
AFM-GT-1000 GPM	AFN-1000 GPM	With JRCP model JRCP-1000 GPM	100
AFM-GT-750-500 GPM	AFN-750-500 GPM at 750	With JRCP model JRCP-750-500 GPM	100
AFM-GT-750-500 GPM	AFN-750-500 GPM at 500	With JRCP model JRCP-750-500 GPM	100
AFM-GT-500 GPM	AFN-500 GPM	Self-inducting	100
Shah Bhogilal Jethilal & Bros			
AAAG FM 500	500 GPM	Self-Inducting	100
Elkhart Brass Mfg Co Inc			
Spit Fire - Model 8394-022	CSW-LB F3.5 set at 500 gpm	Self-Inducting	100
Spit Fire - Model 8394-022	CSW-LB F3.5 set at 750 gpm	Self-inducting	100
Spit Fire - Model 8394-022	CSW-LB F3.5 JP1.5 set at 500 gpm	JRCP type proportioner induction	100
Spit Fire - Model 8394-022	CSW-LB F3.5 JP1.5 set at 750 gpm	JRCP type proportioner induction	100
Spit Fire - Model 8394-062	CSW-LB F4.0 set at 500 gpm	Self-inducting	100
Spit Fire - Model 8394-062	CSW-LB F4.0 set at 750 gpm	Self-inducting	100
Spit Fire - Model 8394-062	CSW-LB F4.0 set at 1000 gpm	Self-inducting	100
Spit Fire - Model 8394-062	CSW-LB F4.0 JP1.5 set at 500 gpm	JRCP type proportioner induction	100

Spit Fire - Model 8394-062	CSW-LB F4.0 JP1.5 set at 750 gpm	JRCP type proportioner induction	100
Spit Fire - Model 8394-062	CSW-LB F4.0 JP1.5 set at 1000 gpm	JRCP type proportioner induction	100
Spit Fire - Model 8394-066	CSW-LB F4.0 set at 500 gpm	Self-inducting	100
Spit Fire - Model 8394-066	CSW-LB F4.0 set at 750 gpm	Self-inducting	100
Spit Fire - Model 8394-066	CSW-LB F4.0 set at 1000 gpm	Self-inducting	100
Spit Fire - Model 8394-066	CSW-LB F4.0 JP1.5 set at 500 gpm	JRCP type proportioner induction	100
Spit Fire - Model 8394-066	CSW-LB F4.0 JP1.5 set at 750 gpm	JRCP type proportioner induction	100
Spit Fire - Model 8394-066	CSW-LB F4.0 JP1.5 set at 1000 gpm	JRCP type proportioner induction	100

PROPORTIONERS-BLADDER TANK WITH CONTROLLER

Description	Controller Size In.	Orifice Size In.	Flow GPM
Firetech Equipment & Systems Private Limited	2	0.28	21 - 264
	3	0.42	56 - 802
	4	0.52	114 - 1623
	6	0.82	267 - 2930
	8	1.30	872 - 3826

FULLBLAZE 6% AFFF, 6 PERCENT

PROPORTIONERS - PORTABLE IN-LINE INDUCTORS

Angus Fire (UK), Model UNI225, 2-1/2 in. size, set at 6, inlet pressure of 149 psi with 30m (98 ft) of 2-1/2 in. hose between inductor and Angus Fire (UK), Model F225U nozzle

NOZZLES

Description	Size In.	Inlet Pressure psi
Angus Fire (UK), Model F225U	2-1/2	85

PROPORTIONERS - FIXED IN-LINE INDUCTORS

Description	Size In.	Orifice Diam In.	Inlet Pressure psi	Back Pressure psi
Angus, Model IND-40	1-1/2	0.28 (7.0 mm)	123	43

FIXED FOAM DISCHARGE OUTLETS

Description		Orifice Diam In.	Inlet Pressure psi
Angus, Model TPS-50MKV		0.59 (15mm)	43
Fuel	Style	Min Application Rate GPM/Sq Ft	Min Inlet Pressure psi
Tyco Fire , Model B1			
Hydrocarbons	Pendant	0.16	30

FULLBLAZE 1% AFFF, 1 PERCENT

PROPORTIONERS - PORTABLE IN-LINE INDUCTORS

Angus Fire (UK), Model UNI225, 2-1/2 in. size, set at 1, inlet pressure of 165 psi with 30 m (98 ft) of 2-1/2 in. hose between inductor and Angus Fire (UK), Model F225U nozzle.

NOZZLES

Description	Size In.	Inlet Pressure psi

Angus Fire (UK), Model F225U	2-1/2	85
------------------------------	-------	----

FULLBLAZE 3% FP, 3 PERCENT

PROPORTIONERS - PORTABLE IN-LINE INDUCTORS

Angus Fire (UK), Model UNI225, 2-1/2 in. size, set at 3, inlet pressure of 142 psi with 30 m (98 ft) of 2-1/2 in. hose between inductor and Angus Fire (UK), Model F225U nozzle.

NOZZLES

Description	Size In.	Inlet Pressure psi
Angus Fire (UK), Model F225U	2-1/2	77

FULLBLAZE 6% FP, 6 PERCENT

PROPORTIONERS - PORTABLE IN-LINE INDUCTORS

Angus Fire (UK), Model UNI225, 2-1/2 in. size, set at 6, inlet pressure of 142 psi with 30 m (98 ft) of 2-1/2 in. hose between inductor and Angus Fire (UK), Model F225U nozzle.

NOZZLES

Description	Size In.	Inlet Pressure psi
Angus Fire (UK), Model F225U	2-1/2	85

FULLBLAZE 3% FFFP, 3 PERCENT

PROPORTIONERS - PORTABLE IN-LINE INDUCTORS

Angus Fire (UK), Model UNI225, 2-1/2 in. size, set at 3, inlet pressure of 11.4 kg/cm² with 100 ft of 2-1/2 in. hose between inductor and Angus Fire (UK), Model F225U nozzle.

NOZZLES

Description	Size In.	Inlet Pressure psi
Angus Fire (UK), Model F225U	2-1/2	85

FULLBLAZE 6% FFFP, 6 PERCENT

PROPORTIONERS - PORTABLE IN-LINE INDUCTORS

Angus Fire (UK), Model UNI225, 2-1/2 in. size, set at 3, inlet pressure of 10.6 kg/cm² with 100 ft of 2-1/2 in. hose between inductor and Angus Fire (UK), Model F225U nozzle.

NOZZLES

Description	Size In.	Inlet Pressure psi
Angus Fire (UK), Model F225U	2-1/2	85

FULLBLAZE 3 X 6 AR-AFFF, 3 PERCENT

PROPORTIONERS - PORTABLE IN-LINE INDUCTORS

Angus Fire (UK), Model UNI225, 2-1/2 in. size, set at 3AR, inlet pressure of 162 psi with 30 m (98 ft) of 2-1/2 in. hose between inductor and Angus Fire (UK), Model F225U nozzle.

NOZZLES

Description	Size In.	Inlet Pressure psi
Angus Fire (UK), Model F225U	2-1/2	85

FULLBLAZE 3 X 6 AR-AFFF, 6 PERCENT

PROPORTIONERS - FIXED IN-LINE INDUCTORS

Description	Size In.	Orifice Diam In.	Inlet Pressure psi	Back Pressure psi
Angus, Model IND-40	1-1/2	0.36 (9.1 mm)	150	62

FIXED FOAM DISCHARGE OUTLETS

Description	Orifice Diam In.	Inlet Pressure psi
Angus, Model TPS-50MKV	0.58(14.8mm)	60

Where:

Fuel	Min Application Rate GPM/Sq Ft
Alc (Alcohols)	0.351

FULLBLAZE ECOPLUS 3 X 3 AR-AFFF

PROPORTIONERS - PORTABLE IN-LINE INDUCTORS

Angus Fire (UK), Model UNI225, 2-1/2 in. size, set at 3AR, inlet pressure of 168 psi with 30 m (98 ft) of 2-1/2 in. hose between inductor and Angus Fire (UK), Model F225U nozzle.

NOZZLES

Description	Size In.	Inlet Pressure psi
Angus Fire (UK), Model F225U	2-1/2	94

PROPORTIONERS - FIXED IN-LINE INDUCTORS

Description	Size In.	Orifice Diam In.	Inlet Pressure psi	Back Pressure psi
Angus, Model IND-40	1-1/2	0.19 (4.8 mm)	119	43

FIXED FOAM DISCHARGE OUTLETS

Description	Orifice Diam In.	Inlet Pressure psi
Angus, Model TPS-50MKV	0.59 (15mm)	43

Where:

Fuel	Min Application Rate GPM/Sq Ft
Alc (Alcohols)	0.17
Methyl Alcohol,	0.10
Ethyl Alcohol	0.10

FOAM WATER SPRINKLERS

Fuel	Style	Min Application Rate GPM/Sq Ft	Min Inlet Pressure psi
Tyco Fire , Model B1			
Hydrocarbons	Pendant	0.16	30
Alc (Alcohols)	Pendant	0.16	30

PROPORTIONERS-BLADDER TANK WITH CONTROLLER

Description	Controller Size In.	Orifice Size In.	Flow GPM
Firetech Equipment & Systems Private Limited	2	0.28	141 - 270
	3	0.42	267 - 828
	4	0.52	442 - 1533
	6	0.82	1105 - 2827
	8	1.30	2801 - 3752

Last Updated on 2014-09-25

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2015 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2015 UL LLC".